



# DATA SHEET

## Filter Standard Line



Type	ID	Possible flanges	Ø A inch	B inch	Weight lbs
KFI 330SL / 206cfm *	151003	4" / 6"	11.8	13.4	24.3
KFI 500SL / 420cfm	151002	6" / 8" / 10"	15.8	19.7	59.5
KFI 660SL / 412cfm *	151004	6" / 8" / 10"	11.8	26.0	46.3
KFI 750SL / 600cfm	151001	6" / 8" / 10" / 12"	15.8	29.5	86.0
KFI 1000SL / 840cfm	151000	8" / 10" / 12"	15.8	39.4	110.2
KFI 1050SL / 1255cfm	154853	14" / 16"	19.7	39.4	118.8
KFI 1250SL / 1020cfm	150999	8" / 10" / 12" / 14"	15.8	49.2	134.5
KFI 1500SL / 1260cfm	150997	10" / 12" / 14"	15.8	59.1	165.4

- Filter Standard Line
- Carbon Filters specifically designed for the control of VOCs, odors, and other gaseous contaminants
- Very low pressure drop
- 2" (\*) / 2.55" carbon bed
- Pelletized activated CKV carbon
- Prefilter included
- Max. operating temp. 80°C / 176°F
- Rated at 0.1 sec. contact time

## Ruck Air Movement - Master Series by



www.mastervent.com marion.pye@mastervent.com

2082 58th Ave. Circle E.  
Bradenton, FL 34203

Phone: 941.739.0879  
Fax: 941.739.0881